

# ★ STARFIRE S-4c



An Effectively Simple, Full-Featured, Heavy Duty 4 yd<sup>3</sup> Broom Sweeper Mounted on a Highly-Maneuverable, Non-CDL Chassis



Proudly American 

  
**STEWART-AMOS**  
Sweeper Co.



# ★ STARFIRE S-4c

- ▶ Highly Productive Performance
- ▶ Rugged and Reliable
- ▶ Extremely Maneuverable


The **S-4c** is a heavy duty, full-featured 4yd<sup>3</sup> dual engine mechanical broom street sweeper that is mounted on a highly-maneuverable cab-over chassis. It's as productive as sweepers mounted on larger chassis yet does not require a CDL to operate. Manufactured with reliability and durability in mind, the **S-4c** is capable of traveling from jobsite to jobsite at highway speeds. Its compact design makes this sweeper the perfect choice for cleaning confined city streets, cul-de-sacs, construction sites, and milling jobs.

The environmentally conscious **S-4c** is SCAQMD PM-10 Rule 1186 Certified.

At Stewart-Amos, we build every sweeper to the highest quality standards that incorporate our *effectively simple* design criteria. With ease of operation, service and maintenance in mind, we engineer and select each component and system to be rugged, reliable and uncomplicated while providing for the most effective and highest sweeping performance.


**We look forward to building one for you. Please contact your local dealer for more information or to arrange a demonstration.**

## The Stewart-Amos Exclusive 3-Shaft Elevator




## S-4c Standard Performance, Productivity & Safety Features:

- 1 200 gallon polyethylene water tank with 3.6 gpm diaphragm pump & elevator wash-down system come standard. Spray nozzles: 2 per curb broom, 4 on main broom & 4 on front spray bar.
- 2 One-piece all steel main frame consists of HD tube and thick liners. This structure allows for rugged & reliable durability.
- 3 Elevator auto pivots up to 10" over fixed obstructions preventing impact damage. No operator judgment required.
- 4 Cast iron gear pump is more tolerant of heat and contaminants, making it simple & economical to troubleshoot, repair or replace.
- 5 59 HP Kubota turbo-charged diesel engine with high temperature/ low oil pressure auto shutdown. This engine is quiet & fuel efficient.
- 6 *Effectively simple* electric-over hydraulic system with built-in hydraulic pressure gauges for ease of service.
- 7 **Extended Chain Life.** 3rd shaft provides proper return (upper) chain support. This allows chains to run as loose as possible dramatically improving chain wear life versus similar 2-shaft designs.  
**Reduced Maintenance Costs.** 3rd shaft provides twice the number of chain adjustment points. Together with reduced chain wear, this significantly reduces maintenance downtime & costs versus 2-shaft designs.  
**Better Loading/Sweeping Performance.** Eliminates chain clapping common in 2-shaft designs. 3rd shaft optimizes chain spacing, reduces clogging & ensures more effective sweeping of large, bulky debris.
- 8 Electric-powered, continuous-running hydraulic oil cooler is vertically-mounted to prevent clogging & provide maximum cooling.
- 9 Color camera system keeps operator facing forward. Sweeper comes standard with dashboard-mounted 7" color monitor with right gutter broom & rear backup cameras. Optional hopper dump observation & hopper inside loading view cameras are available.
- 10 Mounted on a 19,500# GVWR cab-over chassis with short 109" wheelbase. This unit offers extremely tight (16'9") turning radius & excellent forward visibility. Optional air ride suspension is available.
- 11 Larger 36-gallon fuel tank allows for longer run time & increased productivity.
- 12 Front & rear lockable canopies protect components from passing branches, elements & vandalism. Canopies prevent algae growth in the water tank which can clog spray nozzles.







**A Spring-Balanced Brooms**




Spring-balanced, free-floating main & gutter brooms automatically apply correct surface pressure for maximum broom wear life. In-cab gutter broom electric tilt is standard.

**B Ergonomic Controls**




Vertically-mounted control panel is 6-way adjustable for easy & ergonomic viewing. One-touch sweeping allows operator to preset functions. Brooms raise automatically in reverse.

**C Case Drains**



Case drains on all the hydraulic motors protect shaft seals from pressure leaks minimizing repairs & replacements.

**D Simplified Wiring**



Electrical relays & fuses are protected from the elements in a sealed NEMA 4 enclosure. The wiring is heat stamped with numbers for easy identification.

**E Massive Lift Scissors**



Massive double "X" style lift scissors & 4-corner hopper lift ensure exceptional hopper stability when dumping wet, unbalanced, or sticky debris.

**F Off-set Drive Motor**



Off-set hydraulic elevator drive motor is protected against impacts.

**G High Dump Hopper**



Variable dump height hopper (up to 11' high) with 44" extra-long dump door easily reaches most dump trucks.

**H Main Broom Channeler**



Main broom channeler (optional) effectively sweeps large quantities or bulky & light debris (leaves/pine straw). Self-adjusting as main broom wears.

**I Left or Right Side Dump**



Left (street) or Right (curb) side dump available depending on which side best matches your visibility, safety & productivity needs. Dump side must be chosen at time of purchase.

# S-4c SPECIFICATIONS

## General:

Sweeping Path: 10' maximum  
Debris Hopper: 4.0 cubic yards volumetric  
Dump Height (variable): 16' to 132"  
Turning Radius: 16' 9"  
Overall Length: 19' 5"  
Overall Height: 102.5" including strobe lights  
GVWR: 19,500#

## Main Broom:

Length: 58" Diameter: 36"  
Type: Chevron poly-wire combo  
Drive: Hydraulic motor/direct drive & reversible  
Mounting: Full-floating, trailing arm, with shocks  
Lift Control: Hydraulic, in-cab  
Speed: Variable with auxiliary engine rpm  
Dirt Shoes: Carbide, 2" wide

## Dual Gutter Brooms:

Diameter: 42"  
Type: Spring-balanced, auto wear compensating  
Drive: Hydraulic & reversible  
Mounting: Free-floating, trailing arm  
Lift Control: Hydraulic, in-cab  
Tilt control: In-cab (electric)  
Speed: Variable with auxiliary engine rpm  
Dual Float Protected

## Elevator System:

Type: 7-flight squeegee with replaceable rubber edging  
Liner: Bolt-in, 2 piece AR steel plates  
Chain: HD constant radius roller chain  
Sprockets: Urethane  
Shafts: Three  
Drive: Hydraulic, in-cab, & reversible  
Lift Control: Hydraulic, in-cab  
Elevator Stall Warning: Buzzer & light in-cab  
Flushing System: Built-in

## Debris Hopper:

Volumetric Capacity: 4.0 cubic yards  
Dump Height (variable): 16" to 132"  
Hopper Door Reach from Side: 44"  
Inspection door, window, & safety props standard  
4 Corner hopper lift  
Quad (4) double "X" style lift scissors  
Right (curb) side hopper dump

## Hydraulic System:

Pump: Dual tandem gear  
Capacity: 22 gpm @ 2000 rpm  
Reservoir: 40 gallons  
Hydraulic Oil Filter: 10 micron  
Oil Cooler: Electric remote mounted  
Integral hydraulic pressure gauges

## Water Spray System:

Tank Capacity: 200 gallons  
Construction: Polyethylene  
Pump: 3.6 gpm electric diaphragm  
Spray Nozzles:

- 4 on front spray bar
- 2 on each gutter broom
- 4 on main broom

Fill Hose: 20' with NST coupler with anti-siphon air gap  
Water Pump Prefilter: 80 mesh

## Electrical System:

Alternator: 120 AMP Voltage: 12 volt  
LED Lights: front & rear strobes; gutter brooms & rear-mounted working lights; license plate;  
2 stop/turn/tail; & clearance lights  
Backup alarm

## Camera & Monitor Safety System:

7" Color monitor with right side gutter broom & rear backup color cameras

## Instrumentation & Controls:

Sweeper function rocker switches  
Elevator stall alarm & light  
Auxiliary engine hour meter & tachometer  
Electric throttle  
Console night light

## Sweeper Engine:

Make: Kubota V2403-M-T-E3 T4 Interim  
Horsepower: 59 @ 2700 rpm  
Type: in-line, four-cylinder turbo diesel

## Paint:

Body: Standard white high-gloss urethane enamel  
Undercarriage: Flat black enamel

## Standard Accessories:

Auto pickup in reverse  
Auto shutdown for high temperature/low pressure  
Independent left & right gutter broom operation  
36 gallon, common fuel tank  
Operators, parts & maintenance manuals  
Top mounted, front & back amber LED lights

## Limited Warranty Policy:

The Starfire S-4c sweeper is guaranteed to be free from defects due to faulty materials and/or workmanship for a period of 12 months, or 1,000 hours (whichever occurs first). Liability is limited to replacement of defect parts at factory or authorized dealer. The standard warranty of the chassis manufacturer and auxiliary engine applies. Isuzu chassis includes extended 5-year/150,000 mile Isuzu drive-train warranty. *Please read full warranty statement for details and limitations.*

## Available Options: (not included in base price)

Arrow board  
Automatic lubrication systems  
Left (driver-side) hopper dump  
Bristle strips dirt-shoe brushes  
Camera—hopper dump observation  
Camera—hopper inside loading view  
Camera lens washer per location  
Epoxy hopper liner  
Front mounted magnet  
Hopper vibrator  
Hydraulic system—high oil temperature warning  
Hydraulic system—low oil level warning  
Main broom motor guard  
Main broom debris channeller  
On-board high pressure spray wash-down system with hose reel; 50' of hose and wand  
Reverse ultrasonic obstacle detection system  
Strobe light protectors  
Water pump; additional 3.6 gpm

*The Starfire S-4c has built a reputation for rugged, reliability and superior sweeping performance. Let us build one for you. Call your dealer today to arrange for a demonstration.*

Available on:

**HGACBuy**  
THE SMART PURCHASING SOLUTION

**GSA** Schedule  
Contract GS-30F-021AA

Sold and Supported Locally by:

## The Right Sweepers to Match Your Needs

Whatever your sweeping challenge, Stewart-Amos has the right sweeper to match your needs. We offer a full line of *effectively simple* mechanical broom and regenerative air street sweepers.



Harrisburg, PA USA  
800.482.2302  
stewart-amos.com

Specifications are subject to change without notice.  
Copyright © Stewart-Amos Sweeper Co. / 2018